ÆtherBox LITE

ORDER CODE: AETHERBOXLITE



IP RATING	WEIGHT	
IP20	**0,4kg / 0.88lbs**	

MAIN FEATURES

- Single Univers Wireless CRMX Transceiver unit
- Power IN and DMX In/Out through chassis mount connectors and terminal blocks
- Either LumenRadio CRMX and Wireless DMX G3 and G4S transmission option

Downloaded on 14/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

CONTROL

Supported Protocols:	DMX512, RDM, CRMX + WDMX, Bluetooth
RDM:	for remote addressing and parameter configuration
Other:	3 control buttons and status LEDs on-board

ELECTRONICS

Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	screw terminal block, Seetronic powerCON TRUE IN
Signal connection:	screw terminal block, Amphenol XLR 5p IN/OUT connectors
Wireless Connection:	integrated LumenRadio TiMoTwo (full RDM) - CRMX, CRMX² (RX only) and W-DMX compatible
Transmission range:	up to 100 meters in open field

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	5W
Power factor:	> 0,95

INSTALLATION

Suspension and fixing:	track adapter for suspension and fixing (optional)

PHYSICAL

IP rating:	IP20
Housing:	Sturdy polycarbonate body
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	140x60x100mm
Weight:	0,4kg

CERTIFICATIONS / REPORTS

Compliance:	CE, RCM, FCC, cTUVus

BOX CONTENT

1 x AETHERBOXLITE

ACCESSORIES & RELATED PRODUCTS



AETHERBOXONE

IP65 1x universe CRMX transceiver, DMX, Ethernet protocols, Wi-Fi, Bluetooth, battery-ready, POE



UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

Downloaded on 14/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

