ÆtherBox Two

ORDER CODE: AETHERBOXTWO



IP RATING	WEIGHT	
IP65 for temporary outdoor use	**2,2kg / 4.85lbs**	

MAIN FEATURES

- IP65 double universes CRMX transceiver
- XLR 5p in/out, Ethernet for sACN and ArtNet, as well as Wi-Fi and Bluetooth
- Rack mounting, truss mounting, camlocks, M10 and ⅜ threads anchoring options
- Main power DC12V input, POE and NP-F battery type operation via an adapter box accessory
- Available operating modes: TX mode, RX mode, and Repeater mode
- Compatible with: CRMX, G4S, G3, and CRMX2 - CRMX2 operates as a receiver only

Downloaded on 14/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

CONTROL

Supported Protocols:	DMX512, RDM, ArtNet, sACN, CRMX
DMX channels:	1024ch
RDM:	for remote addressing and parameter configuration
Display:	Graphic User Interface
Other:	1 push encoder

CONNECTIONS

Power connection:	Seetronic powerCON TRUE IP65 IN
Signal connection:	Seetronic XLR 5p IN/OUT connectors
Wireless Connection:	2x integrated LumenRadio TiMoTwo (full RDM) - CRMX, CRMX² (RX only) and W-DMX compatible
Transmission range:	up to 80 meters with the included AEB2DBA90D antenna in open field
Data connection:	Seetronic Ethernet IP IN connector
Low Voltage DC connector:	Weipu SA6(12-48V), Battery slots

PHYSICAL

IP rating:	IP65 for temporary outdoor use
Housing:	Weatherproof IP65 construction
Finish:	black
Operating temperature:	Ta -20 to +45 °C (-4 to +113 °F)
Dimensions (WxHxD):	270x45x241mm
Weight:	2,2kg

ELECTRONICS

Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

BATTERY

Battery:	2x7,2V NP-F550/F570/F750/F770 type battery via dedicated accessory

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Low Voltage DC mains:	12V via DC IN, 2x7.2V via battery slots, POE
Max power consumption (230V):	5W
Standby power:	1,4 W

INSTALLATION

Rack mount:	1U 19" standard rack (optional accessories)
Mounting points:	M10 and 3/8" threaded mounting points for clamps and wall mounting

CERTIFICATIONS / REPORTS

Compliance:	CE, RCM, FCC, cTUVus

BOX CONTENT

1 x AETHERBOXTWO

2 x AEB2DBA90D

1,5 meters 3G1,5mmq power cable (BARE END - SEETRONIC POWERCON TRUE1 IP65 power connector)

Downloaded on 14/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



AEB2DBA90D
2 dBi 90° angled antenna (N-male connector) for AETHERBOX and CRMXBOXIP67, up to 80 m



AEB2DBA
2 dBi Omni antenna (RP-TNC male connector) for AETHERBOX and CRMXBOXIP67, up to 80 m



AEB5DBALR
Long range 5dB antenna for AETHERBOX series, N-male connector, up to 850 m



AEBTWOBAG1U
Empty ABS case for 1 pc of AETHERBOXTWO



CRMXBOXIP6790ADP
IP67 90 degree adapter for CRMXBOXIP67 / AETHERBOX antenna, N-male connector



CABEXTN2N01M
Antenna extension cable for AETHERBOX and CRMXBOXIP67, N-female connectors, 1 m, 10% lost



CABEXTN2N05M
Antenna extension cable for AETHERBOX and CRMXBOXIP67, N-female connectors, 5 m, 30% lost



CABEXTN2N15M
Antenna extension cable for AETHERBOX and CRMXBOXIP67, N-female connectors, 15 m, 70% lost



OS27PLUS
Quick-Lock omega bracket, M12 hole



AETHERBOXONE
IP65 1x universe CRMX transceiver, DMX, Ethernet protocols, Wi-Fi, Bluetooth, battery-ready, POE

AEB5DBA
5dB antenna for AETHERBOX and CRMXBOXIP67, N-male connector, up to 80 m



AEB2DBA90DLR
Long range 2 dBi 90° angled antenna (N-male connector), AETHERBOX series, up to 600 m



AEB2DBALR
Long range 2 dBi Omni antenna (RP-TNC male connector), AETHERBOX series, up to 500 m



AEBBATADP
Battery holder for AETHERBOX



AEBRP2TNC
RP-TNC Female to N Male Adapter for AETHERBOX and CRMXBOXIP67



CABEXTN2N03M
Antenna extension cable for AETHERBOX and CRMXBOXIP67, N-female connectors, 3 m, 20% lost



CABEXTN2N10M
Antenna extension cable for AETHERBOX and CRMXBOXIP67, N-female connectors, 10 m, 55% lost




AEBTWORACKADP
Rack adapter for AETHERBOXTWO




UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector


TECHNICAL DRAWINGS




All dimensions are in mm / in
Le misure sono espresse in mm / in


AEBBATADP





AEBTWORACKADP





PROLIGHTS		Drawing number / Disegno numero: 01	
Title / Titolo: AETHERBOXTWO		Draw description / Descrizione disegno: With accessories	
Date / Data: 16-09-2025	Revision N. / Versione N°: 001	Sheet / Foglio: 01 of / di 01	Checked / Controllato

Duplication of this drawing, either full or in part, is strictly prohibited without prior written authorization of Music&Lights
Questo disegno non può essere copiato, riprodotto, mostrato a terzi senza autorizzazione della Music&Lights