Air 18Z

ORDER CODE: AIR18Z



SOURCE

18x15W RGBW Osram Ostar LEDs

ZOOM RANGE

6° - 66° motorised linear zoom

IP RATING

IP20

WEIGHT

13kg / 28.66lbs

Downloaded on 08/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	18x15W RGBW Osram Ostar LEDs
Luminous flux:	8'800
Lux:	(6°) 17'230 lx - (66°) 1'649lx @3 m full
Source life expectancy:	> 50.000 h

OPTICS

Zoom range:	6° - 66° motorised linear zoom
Lens type:	honeycomb gapless plano-convex optics

COLOUR SYSTEM

CCT:	CCT control through dedicated DMX channel
White presets:	2.800 K ~ 9.000K
Colour wheel:	virtual colour wheel with macros

DYNAMIC EFFECTS

Pixel patterns:	pre-programmed static and dynamic pixel patterns
FX generator:	adjustable foreground/background colour, index, speed, direction
Special features:	Pixels controlled through On/Off switch for simplified control and budget friendly

CONTROL

Supported Protocols:	DMX512, RDM
DMX channels:	25 / 27 / 36 / 99ch
Pixel control:	pixel2pixel control through on/off switch
RDM:	for remote addressing and parameter configuration
Display:	LCD high resolution colour display
Hibernation:	power safe mode when lost DMX
Master/Slave:	for synchronised operation of more units linked in a chain

MOVEMENT

Pan:	630° - 8/16-bit resolution with 360° endless rotation
Tilt:	265° - 8/16-bit resolution
Position feedback:	automatic repositioning after external movement

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Strobe / shutter:	1 - 25 Hz, electronic
Display battery:	included, self-charging battery backup
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX2 (not included)

CONNECTIONS

Power connection:	powerCON TRUE1 IN/OUT
Signal connection:	XLR 5p IN/OUT connectors
Wireless Connection:	optional W-DMX receiver

Downloaded on 08/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	270W
Output (at 230V):	8 units on a single power line
Standby power:	20W

PHYSICAL

IP rating:	IP20
Cooling:	heat pipe with low-noise fan
Housing:	Aluminium structure with high-resistance polycarbonate cover
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	550x342x200mm
Weight:	13kg

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

BOX CONTENT

1 x AIR18Z

1 x 1,5 meters 3G1,5mmq power cable (BARE END - NEUTRIK POWERCON TRUE1 IP65 power connector)

2 x OS24PLUS

ACCESSORIES & RELATED PRODUCTS



OS24PLUS
Quick-lock omega bracket, M12 hole



FCLAIR18Z
Flight case for 4pcs of AIR18Z



UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

Downloaded on 08/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

