Apix 3

ORDER CODE: APIX3



IP RATING		
IP40		

MAIN FEATURES

- Rental-friendly die-cast aluminium housing
- Black-face LEDs for high-contrast and superb colour consistency
- Magnetic front access LED display modules for fast and easy maintenance
- Flicker-free on camera
- High-performance video reproduction at every level of brightness
- 160° viewing angle
- CE and EMC certified by TUV

Downloaded on 23/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

VIDEO

LED source:	SMD 2020 high-power FC black face
Pixel pitch:	3.9 mm
Panel resolution:	128x128pixels
Module resolution:	64x64pixels
Luminous flux:	1.200nit
Grayscale:	16 bit
Refresh rate ≥:	1.920Hz
Drive Mode:	1/16 scan, constan current
Vertical viewing angle:	160°
Horizontal viewing angle:	160°
LED density:	65.746LED/sqm
Dead Pixel Ratio:	<0,002
LED avg life span:	100.000 h

ELECTRICAL

Power input/output:	powerCON
Power supply:	AC 110/230 V 50/60 Hz
Max power consumption (panel):	180W
Avg power consumption (panel):	60W
Max power consumption (sqm):	720W
Avg power consumption (sqm):	240W
Standby power consumption (pannello):	10,2W
Max rated current/panel::	AC 220 V / 0,8 A
Max power output:	8modules
Working temperature:	-10 ~ +40°C
Working humidity:	10 - 90%

CONTROL

Control protocol:	Novastar
Signal input:	RJ45
Signal output:	RJ45

MECHANICS

Module size (WxH):	250x250mm
Panel size(WxHxD):	500x500x90mm
Vertical hanging system:	built-in aliscaf clamp support
Connection:	seamless locking system
Panel weight:	8kg
Weight per square meter:	32kg
Hanging Panel Quantity ≤:	20

PHYSICAL

IP rating:	IP40
Cooling:	fan-free with natural convection
Housing:	Die-cast aluminium housing
Finish:	black

CERTIFICATIONS / REPORTS

Compliance:	CE

Downloaded on 23/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



AP2366CASE
Flight case for 6pcs APIX series LED display, 600x755x795 mm



AP236XJ
Metal joint used to connect 4 APIX2, 3, 6, 4T, modules, M10 hole for clamp



APOS
Shackle for APIX hanging systems, max load 200 kg



AP236ACL01
Power cable for APIX2, APIX3, APIX6, L.110 cm



AP236DCL01
Data cable for APIX2, APIX3, APIX6, assembled with RJ45, L.110 cm



APIX600GSB2
APIX ground stacking system, PRO version (up to 6 m), double base



APIX600GSBS
APIX ground stacking system, PRO version (up to 6 m), queer back support



APIX600GSBV
APIX ground stacking system, PRO version (up to 6 m), base unit vertical

Downloaded on 23/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

