
ArcShine 12

ORDER CODE: ARCSHINE12FC



VERSIONS

Code	Color Synthesis
ARCSHINE12FC	**Full Color**
ARCSHINE12TU	Tungsten
ARCSHINE12DY	Daylight

SOURCE
12x8W RGBW LEDs

IP RATING
IP66 for outdoor installations

WEIGHT
8,8kg / 19.4lbs

Downloaded on 22/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	12x8W RGBW LEDs
Luminous flux:	2'995
Lux:	(15°) 1'182lx @5 m full
Lux:	(45°) 175lx @5 m full
Source life expectancy:	> 50.000 hrs (L70B10 @Ta 25° C / 77° F)

OPTICS

Beam angle:	15°
Field angle:	22°
Additional optics:	25° - 45° (optional)

COLOUR SYSTEM

White presets:	3.200 K ~ 10.000K
Colour wheel:	virtual colour wheel with macros
Macros:	several pre-built macros with adjustable speed

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512
DMX channels:	4 / 6 / 10 / 48 / 53ch
Pixel control:	pixel2pixel control
Display:	touch - sensitive LED display
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 ~ 30 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	1,8 m moulded IP signal IN/OUT connectors
Signal connection:	1,8 m moulded IP signal IN connector
Adaptors:	XLR and BARE END 16A adaptors included

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	108W
Output (at 230V):	18 units on a single power line

PHYSICAL

IP rating:	IP66 for outdoor installations
Cooling:	pressure equalisation through GORE membrane vents
Housing:	Sturdy die-cast aluminium body
Finish:	white (RAL 9003)
Operating temperature:	Ta -20 to +45 °C (-4 to +113 °F)
Dimensions (WxHxD):	990x200x187mm
Weight:	8,8kg

INSTALLATION

Suspension and fixing:	bracket for hanging and floor positioning

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 22/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x ARCSHINE12

1 x 0,28 meters 3G1,5mmq power cable (BARE END - IP connection adapter)

1 x 5p XLR - IP connection male adapter

1 x 5p XLR - IP connection female adapter

ACCESSORIES & RELATED PRODUCTS



CRMXBOXIP67

IP67 1 Universe CRMX Wireless Transceiver for exterior installation



ARCLUMIL15D42

Optic lens 22°, D.42mm



ARCLUMIL25D42

Optic lens 25°, D.42mm



ARCLUMIL45D42

Optic lens 45°, D.42mm



AWEXAC12ADP

Power adapter from AWEXAC1 cable series to AWEXAC2 cable series



AWEXDC1221ADP

Signal adapter kit from AWEXDC1 series to AWEXDC2 series and vice versa




UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector


Downloaded on 22/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS




PHOTOMETRICS

Full On - 15°



Beam angle (50%): **17.2°**	Field angle (10%): **29.8°**	Cut-off angle (2.5%): **39°**


Full On - 25°



Beam angle (50%): **23.4°**	Field angle (10%): **40.9°**	Cut-off angle (2.5%): **53.2°**

Downloaded on 22/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

Full On - 45°



Beam angle (50%): **42°**	Field angle (10%): **79.3°**	Cut-off angle (2.5%): **105.6°**

MUSIC & LIGHTS S.r.l. | Via A. Olivetti, snc
04026 - Minturno (LT) ITALY | info@prolights.it
Tel: +39 0771 72190 | **prolights.it**
VAT No. IT 02057590594

Downloaded on 22/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice