ArcShine S9FC

ORDER CODE: ARCSHINES915FC

5 YEARS Warranty



SOURCE	IP RATING	WEIGHT
9x2W RGB + Warm White LEDs	IP66 for outdoor installations	1,95kg / 4.3lbs

LUMINOUS FLUX (MAX)	CRI
744 lm	>80

Downloaded on 16/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	9x2W RGB + Warm White LEDs
Luminous flux:	(15°) 655 lm; (15°+20°) 638 lm; (15°+60°) 618 lm; (15°+10°x60°) 744 lm; (15°+30°x60°) 644 @Full
Lux:	(15°) 428 lx; (15°+20°) 146 lx; (15° +60°) 51 lx; (15°+10°x60°) 102 lx; (15°+30°x60°) 64lx @3 m full
CRI:	>80
Source life expectancy:	> 50.000 hrs (L70B10 @Ta 25° C / 77° F)

OPTICS

Beam angle:	15°
Additional optics:	see available accessories

COLOUR SYSTEM

CCT:	CCT control through dedicated DMX channel
Colour wheel:	virtual colour wheel with macros
Macros:	built-in white presets

MOVEMENT

Tilt:	180° with manual adjustment

CONTROL

Supported Protocols:	DMX512, RDM
DMX channels:	1 / 2 / 5 / 9 / 12 / 14ch
RDM:	for remote addressing and parameter configuration
Display:	user interface through DATAMASTER external coder (not included)
Stand Alone:	available through DATAMASTER external coder (not included)
Master/Slave:	for synchronised operation of more units linked in a chain
Other:	16bit control of dimmer and colour

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1-30 Hz, electronic
Selectable PWM:	600 to 25,000 Hz (selectable steps)
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	moulded IP power IN/OUT connectors
Signal connection:	moulded IP signal IN/OUT connectors
Adaptors:	XLR and BARE END 16A adaptors included

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	21W
Output (at 230V):	58 units on a single power line
Power factor:	>0,95

PHYSICAL

IP rating:	IP66 for outdoor installations
IK rating:	IK09 impact rating
Cooling:	fan-free with natural convection
Housing:	Sturdy aluminium profile
Finish:	basalt grey (RAL 7012)
Operating temperature:	Ta -20 to +45 °C (-4 to +113 °F)
Dimensions (WxHxD):	500x150x64,7mm
Weight:	1,95kg

INSTALLATION

Suspension and fixing:	double bracket for hanging and floor positioning

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM, cTUVus, FCC

Downloaded on 16/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x ARCSHINES9FC

1 x 0,3 meters 3G1mmq power cable (BARE END - IP connection adapter)

1 x 5p XLR - IP connection male adapter

1 x 5p XLR - IP connection female adapter

ACCESSORIES & RELATED PRODUCTS



AETHERLINK
IP66 rated 1 Universe CRMX wireless transceiver for permanent outdoor installation



AWEXAC2L03
Extension IP67 power cable, IPpowercon-F -> IPpowercon-M, 3m



AWEXAC2L05
Extension IP67 power cable, IPpowercon-F -> IPpowercon-M, 5m



AWEXAC2L10
Extension IP67 power cable, IPpowercon-F -> IPpowercon-M, 10m



AWEXAC2L20
Extension IP67 power cable, IPpowercon-F -> IPpowercon-M, 20m



AWEXDC2L03
Extension IP67 signal cable, IPdataCON-F -> IPdataCON-M, 3m



AWEXDC2L05
Extension IP67 signal cable, IPdataCON-F -> IPdataCON-M, 5m



AWEXDC2L10
Extension IP67 signal cable, IPdataCON-F -> IPdataCON-M, 10m



AWEXDC2L20
Extension IP67 signal cable, IPdataCON-F -> IPdataCON-M, 20m



ARCS9FIXBD
Barndoor to adjust the light beam for ARCSHINES9 and ARCSHINEM9



ARCSS9FILTER20
Light diffusion filter for ARCSHINES9, 20°



ARCSS9FILTER40
Light diffusion filter for ARCSHINES9, 40°




ARCSS9FILTER60
Light diffusion filter for ARCSHINES9, 60°



ARCSS9FILTER1060
Light diffusion filter for ARCSHINES9, 10°x60° (VxH)



ARCSS9FILTER3060
Light diffusion filter for ARCSHINES9, 30°x60° (VxH)



ARCSSM9OUTERCASE
Outercase box for ground installation for ARCSHINES9 and ARCSHINEM9 series, manual tilt



AWEXDC1221ADP
Signal adapter kit from AWEXDC1 series to AWEXDC2 series and vice versa




AWEXAC12ADP
Power adapter from AWEXAC1 cable series to AWEXAC2 cable series




UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS



PHOTOMETRICS

Full on - 15°



Beam angle (50%): **15.5°**	Field angle (10%): **41.1°**	Cut-off angle (2.5%): **72.3°**

MUSIC & LIGHTS S.r.l. | Via A. Olivetti, snc
04026 - Minturno (LT) ITALY | info@prolights.it
Tel: +39 0771 72190 | **prolights.it**
VAT No. IT 02057590594

Downloaded on 16/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice