Chroma Rock

ORDER CODE: CHROMAROCK



SOURCE	IP RATING	WEIGHT
25(5x5) x 10W RGBW Osram LED	**IP20**	**14kg / 30.86lbs**

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	25(5x5) x 10W RGBW Osram LED
Luminous flux:	8'280
Lux:	40'000lx @3 m
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	9°
Field angle:	15°

COLOUR SYSTEM

CCT:	CCT control through dedicated DMX channel
White presets:	2.800 K ~10.000K
Colour wheel:	virtual colour wheel with macros
Macros:	several pre-built pixel macros with adjustable speed

DYNAMIC EFFECTS

Pixel patterns:	pre-programmed static and dynamic pixel patterns
FX generator:	adjustable foreground/background colour, index, speed, direction

GOBOS

Gobo wheel 1:	alphanumeric pattern with index and rotation control

CONTROL

Supported Protocols:	DMX512, Art-Net, Kling-Net
DMX channels:	9 / 10 / 13 / 18 / 23 / 81 / 106 / 113 / 119ch
Pixel control:	pixel2pixel control
Display:	Graphic User Interface
Master/Slave:	for synchronised operation of more units linked in a chain

MOVEMENT

Pan:	540° - 8/16-bit resolution
Tilt:	270° - 8/16-bit resolution
Position feedback:	automatic repositioning after external movement
Pan / tilt lock:	for transport and maintenance

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	selectable dimming modes available
Strobe / shutter:	1 - 20 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	Neutrik XLR 3p + 5p IN/OUT connectors

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	412W
Output (at 230V):	8 units on a single power line

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

PHYSICAL

IP rating:	IP20
Cooling:	heat pipe with low-noise fan
Housing:	Aluminium structure with high-resistance polycarbonate cover
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	379x471x288mm
Weight:	14kg

BOX CONTENT

1 x CHROMAROCK

1 x 1,5 meters power cable (BARE END - SEETRONIC power connector)

2 x quick-lock omega brackets

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

ACCESSORIES & RELATED PRODUCTS



UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS

