ControlGo

ORDER CODE: CONTROLGO



IP RATING	WEIGHT	
IP20	**0.6kg / 1.32lbs**	

MAIN FEATURES

- One Universe DMX Controller , RDM controller, DMX recorder, Remote UI
- 5'' touchscreen with 4 RGB encoders and physical buttons for unprecedented user experience
- Signal output through XLR, Wireless CRMX, and remote UI connector
- Power sources: NP-F batteries (batteries not included), V-mount adapter plate, 48V DC remote UI, 12-48V DC input through SF6-M 4p, USB type-C 5-12V power input (power cable not included)

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

CONTROL SURFACE

On-board Screen:	5” Full Color Touchscreen

CONNECTIVITY

DMX out:	1 universe

ELECTRONICS

Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included), via USB pen drive or onboard memory

CONNECTIONS

Signal connection:	Seetronic XLR 5p OUT connector
Wireless Connection:	integrated LumenRadio TiMoTwo - CRMX, CRMX² (RX only) and W-DMX compatible
Data:	1x USB-A port
Low Voltage DC connector:	Weipu SA6(12-48V), Weipu SA12 (48V - RemoteConnector), USB type C PD3.0, Battery slots

PHYSICAL

IP rating:	IP20
Cooling:	passive, fan-free
Housing:	Sturdy polycarbonate body
Finish:	black
Weight:	0.6kg

BOX CONTENT

1 x CONTROLGO

1 x CTRGEVACASE

2 x CTRGHANDLE

1 x CTRGNL

1 x PRLUSBCL015

SOFTWARE

DMX Channels:	512ch

CONTROL

Supported Protocols:	DMX512, RDM, CRMX + WDMX
DMX channels:	512ch
RDM:	for remote addressing and parameter configuration
Display:	5" Touch LCD
Other:	4 rotary push-encoders with RGB backlight

BATTERY

Battery:	7.2V NP-F550/F570/F750/F770/ F960/F970 type battery or V-Mounts (14.4V) via dedicated accessory
Other:	Batteries not included with the device.

ELECTRICAL

Low Voltage DC mains:	12-48V via DC IN, 48V via Remote Connector, 5-9-12-20V via PD3.0 over USB-C, 7.2V via battery slots
Max power consumption (230V):	8W

CERTIFICATIONS / REPORTS

Compliance:	CE, RCM, FCC, cTUVus

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



CTRGEVACASE
Eva Case for CONTROLGO



CTRGHANDLE
Soft handle for CONTROLGO (1pcs)



CTRGNL
Neck lanyard with double balancing and adjustable side strips for CONTROLGO



PRLUSBCL015
USB-C to USB-C cable, 1,5 meter lenght



CTRGABSC
Empty ABS case for CONTROLGO



CTRGVMADP
V-Mount adapter for CONTROLGO



CTRGQMP
Quick mount plate for CONTROLGO



CTRGCABLE
WEIPU SA12 7,5 m cable for CONTROLGO

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

