DigiDriver IP

ORDER CODE: DIGIDRIVERIP



IP RATING	WEIGHT	
IP65 for temporary outdoor use	**4.5kg / 9.92lbs**	

MAIN FEATURES

- Art-Net, Kling-Net and sACN control protocol supported
- Power and signal output up to 20 DigiStrip IP100 or 40 DigiStrip IP50
- IP65 for outdoor events
- Firmware update with NET cable without interface

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

CONTROL

Supported Protocols:	Art-Net, sACN, Kling-Net
Control units:	20 x DIGISTRIPIP100 or 40 x DIGISTRIPIP50
Art-Net channels:	20x512ch
Pixel control:	pixel2pixel control
Display:	Graphic User Interface

CONNECTIONS

Power connection:	Seetronic powerCON waterproof IN/OUT connectors
Signal connection:	2xRJ45 and 4p out

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	550W
Output (at 230V):	5 units on a single power line

PHYSICAL

IP rating:	IP65 for temporary outdoor use
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta -20 to +45 °C (-4 to +113 °F)
Dimensions (WxHxD):	483x84x250mm
Weight:	4.5kg

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets
Rack mount:	2U 19" standard rack

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA

BOX CONTENT

1 x DIGIDRIVERIP

1 x 1,5 meters power cable (BARE END - SEETRONIC IP65 power connector)

ACCESSORIES & RELATED PRODUCTS



OS25PLUS

Quick-lock omega bracket, M12 hole

DIGICABLEIP

DIGI IP series signal 4-pin cable

DIGILINKIP

Digi IP series signal 4-pin cable

TECHNICAL DRAWINGS

