DisplayCob WW

ORDER CODE: DISPLAYCOBWW



SOURCE	IP RATING	WEIGHT
45W White COB LED	IP20	1,85kg / 4.08lbs

CRI
>96

Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	45W White COB LED
Source CCT:	3.200K
Luminous flux:	(30°) 2'171 - (60°) 2'309 @Full
Lux:	(30°) 236lx @5 m full
Lux:	(60°)lx
CRI:	>96
R9:	>82
TLCI:	>97
TM30 Rf:	>94
TM30 Rg:	100
Source life expectancy:	> 50.000 hrs (L70B10 @Ta 25° C / 77° F)

OPTICS

Beam angle:	60°
Field angle:	80°
Lens type:	parabolic reflector in combination with HD fresnel lens
Additional optics:	30° (inc) - 15° (opt)

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of dimmer and strobe
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512
DMX channels:	1 / 2 / 5ch
Display:	Graphic User Interface
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 - 28 Hz, electronic
Selectable PWM:	600 to 25,000 Hz (selectable steps)
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	moulded IP power IN connector
Signal connection:	XLR 5p IN/OUT connectors

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	52W
Output (at 230V):	29 units on a single power line
Power factor:	>0,98

PHYSICAL

IP rating:	IP20
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	166x118x250mm
Weight:	1,85kg

INSTALLATION

Suspension and fixing:	double bracket for hanging and floor positioning

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

BOX CONTENT


1 x DISPLAYCOBWW

Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



DISPLAYCOBL30
Optics for DISPLAYCOB projectors series, 30°



DISPLAYCOBL15
Optics for DISPLAYCOB projectors series, 15°




DISPLAYCOBBDBK
Barn door with 4 directional flaps to adjust the light beam, for DISPLAYCOB, BK



UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector


Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS




PHOTOMETRICS

Full on - 15°




Beam angle (50%): **17.2°**	Field angle (10%): **30.1°**	Cut-off angle (2.5%): **67.3°**

Full on - 30°



Beam angle (50%): **27.4°**	Field angle (10%): **56.9°**	Cut-off angle (2.5%): **106.1°**

Full on - 60°



Beam angle (50%): **52.3°**	Field angle (10%): **88°**	Cut-off angle (2.5%): **125.2°**

MUSIC & LIGHTS S.r.l. | Via A. Olivetti, snc
04026 - Minturno (LT) ITALY | info@prolights.it
Tel: +39 0771 72190 | **prolights.it**
VAT No. IT 02057590594

Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice