Dot QPack

ORDER CODE: DOTQPACKMR



SOURCE	IP RATING	WEIGHT
1x15W RGBW LED	**IP65 (front) - IP54 (bottom) for temporary outdoor use**	**6kg / 13.23lbs**

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	1x15W RGBW LED
Luminous flux:	550
Lux:	710lx @3 m full
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	15°
Field angle:	23°
Additional optics:	Magnetic Frost filter included for wider diffusion

COLOUR SYSTEM

White presets:	2.800-9.000K
Colour wheel:	virtual colour wheel with macros
Macros:	built-in white presets

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	W-DMX, RDM
DMX channels:	5 / 9ch
RDM:	for remote addressing and parameter configuration
Display:	3 chars display
IR:	infrared remote controller for simple control, addressing and settings

MOVEMENT

Tilt:	° with adjustable foot support

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Strobe / shutter:	1-25 Hz, electronic

BATTERY

Battery:	11,1V lithium
Battery life in colour change mode up to:	16h
Battery life in full-mode up to:	6h
Recharge connection:	power cable fast-charge in pelican case
Recharge time:	3h (max)
Battery level indicator:	LED battery status indicator

CONNECTIONS

Wireless Connection:	integrated W-DMX receiver

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz

PHYSICAL

IP rating:	IP65 (front) - IP54 (bottom) for temporary outdoor use
Cooling:	fan-free with natural convection
Housing:	Sturdy polycarbonate body
Finish:	mirror finishing
Operating temperature:	Ta 0 to +35 °C (+32 to +95 °F)
Dimensions (WxHxD):	520x125x320mm
Weight:	6kg

INSTALLATION

Suspension and fixing:	bracket for hanging and floor positioning
Hardware on-board:	air suckers, eye bolts, top hat, rubber feets (included in DOTQPACK)

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM, cTUVus, FCC

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x ABS pellican case

6 x DOTQ

1 x DOTQIRC

6 x hanging brackets

12 x air suckers

6 x eye bolt

6 x magnetic frost filters

6 x top hat

24 x rubber feets

1 x 6 ways battery charger

1 x 1,5 meters BARE END - IEC power cable

ACCESSORIES & RELATED PRODUCTS



AETHERBOXONE

IP65 1x universe CRMX transceiver, DMX, Ethernet protocols, Wi-Fi, Bluetooth, battery-ready, POE



DOTQIRC

IR remote controller for DOTQ

MUSIC & LIGHTS S.r.l. | Via A. Olivetti, snc 04026 - Minturno (LT) ITALY | info@prolights.it Tel: +39 0771 72190 | **prolights.it** VAT No. IT 02057590594

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice