EclFresnel CT+LIP

ORDER CODE: **ECLFRCTPLIPBK**



SOURCE	ZOOM RANGE	IP RATING
600W 6 colour LEDs source	**10° - 77° manual**	**IP65 for temporary outdoor use (*)**

WEIGHT	LUMINOUS FLUX (MAX)	CRI
19,1kg / 42.11lbs	**7'706 lm**	**97,8 @3.200K**

Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	600W 6 colour LEDs source
Luminous flux:	(10°) 7'706 lm - (77°) 16'165 @Full
Lux:	(10°) 7'873 lx - (77°) 845lx @5 m full
CRI:	97,8 @3.200K; 97,4 @5.600 K
R9:	91 @3200K; 92 @5.600 K
TLCI:	91 @3200K; 95 @5.600 K
TM30 Rf:	> 94 @3.200K; > 94 @5.600 K
TM30 Rg:	< 100 @3.200K; < 101 @5.600 K
Source life expectancy:	> 50.000 h

OPTICS

Zoom range:	10° - 77° manual
Lens diameter:	250mm
Lens type:	AR-coated glass Fresnel lens providing a classic soft light fall-off
Other:	spigot, barndoor and gel frame included

COLOUR SYSTEM

Colour control:	XY, CCT, Gel with Source Emulation, Tungsten emulation, HSI, User preset
CCT:	linear CCT adjustment from 1.850 K-20.000K

CONTROL

Supported Protocols:	DMX512, RDM, CRMX
RDM:	for remote addressing and parameter configuration
Display:	2.8'' Color display
Stand Alone:	4 pushable RGB backlit encoder
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	6 selectable dimming modes available
Strobe / shutter:	1 - 30 Hz, electronic
Selectable PWM:	1,282 to 40,000 Hz (selectable steps)
Firmware upgrade with:	via DMX with UPBOXPRO (not included)

CONNECTIONS

Power connection:	Seetronic powerCON TRUE IP65 IN/OUT
Signal connection:	IP65 Seetronic XLR 5p IN/OUT connectors
Wireless Connection:	integrated LumenRadio TiMoTwo - CRMX, CRMX² (RX only) and W-DMX compatible
Data connection:	IP65 WEIPU SF12 4P-F
Low Voltage DC connector:	XLR 3p for 48V

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Low Voltage DC mains:	48V
Max power consumption (230V):	600W
Output (at 230V):	5 units on a single power line
Power factor:	> 0,94

Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

PHYSICAL

IP rating:	IP65 for temporary outdoor use (*)
Cooling:	heat pipe with low-noise fan
Housing:	Weatherproof IP65 construction with die-cast magnesium alloy
Finish:	black (RAL 9004)
Operating temperature:	Ta -20 to +45 °C (-4 to +113 °F)
Dimensions (WxHxD):	420x663x495mm
Weight:	19,1kg

(*)

NOTE:	Suitable for permanent outdoor use, provided that installation and periodic maintenance are carried out by qualified technicians.

INSTALLATION

Bracket system:	Sliding bracket for adjustable weight balance
Hardware on-board:	filter frame, 8-leaf barndoor and spigot
Other:	strengthened zoom movement system for enhanced durability and stability

CERTIFICATIONS / REPORTS

Compliance:	CE, RCM, FCC, cTUVus

BOX CONTENT

1 x ECLFRCTPLIP

1 x ECLFRSPG

1 x ECLFRCTPLFF

1 x ECLFRCTPLBD

1 x 1,5 meters 3G1,5mmq power cable (BARE END - SEETRONIC POWERCON TRUE1 IP65 power connector)

ACCESSORIES & RELATED PRODUCTS



ECLFRCTPLAHK
Longer accessory holder kit for ECLFRCTP series



ECLFRCTPLBAG1U
Empty ABS case for 1 pc of ECLFRCTPL / LIP series



FCLECLFRCTPL
Flight case for 2 pcs of ECLFRCTPL / LIP series



FCLECLFRCTPLR2
Flight case for 2 pcs of ECLFRCTPL / LIP series



ECLFRCTPLKPOYO
Pole operated aluminium yoke bracket and zoom kit for ECLFRCTPL series



ECLFRSPG
Spigot for PROLIGHTS fixtures



ECLFRCTPLFFBK
Filter frame for ECLFRCTPSL series, black




ECLFRCTPLBDBK
Barn door 8 directional flaps to adjust the light beam for ECLFRCTPL




UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS




PHOTOMETRICS

Full On - HQ - RAW - Min Zoom



Beam angle (50%): **9.8°**	Field angle (10%): **17.9°**	Cut-off angle (2.5%): **25°**

Full On - HQ - RAW - Max Zoom



Beam angle (50%): **56.4°**	Field angle (10%): **76.9°**	Cut-off angle (2.5%): **85.6°**

Downloaded on 09/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice