EdgeGo

ORDER CODE: **EDGEGO**



IP RATING	WEIGHT	
IP20	**4,1kg / 9.04lbs**	

TECHNICAL SPECIFICATIONS

CONTROL SURFACE

On-board Screen:	10.1” Full Color Touchscreen
Playback Faders:	6 linear faders
Playback Encoders:	6 rotary push-encoders with RGB backlight
Value Encoders:	8 rotary push-encoders with RGB backlight

SOFTWARE

DMX Channels:	2048ch
DMX universes:	4 DMX universes freely mappable between CRMX, DMX, ArtNet, s-ACN
Playback Pages:	99 + 1 Template Page
Memories:	250 Presets per Feature Group, 100 Fixture-Groups
Max Fixtures:	Limited by DMX Channels
External Control:	MIDI trigger. MIDI Timecode, OSC
Software update:	via USB stick or online server (requires internet connection)
Library update:	via USB stick or online server (requires internet connection)

CONNECTIVITY

DMX out:	2 freely mappable
ArtNet:	4 universes, freely mappable
sACN:	4 universes, freely mappable
MIDI:	In / Through / Out
Wireless:	2x DMX universes freely assignable to any of the TimoTwo LumenRadio modules - CRMX or W-DMX, with Bluetooth support
External Display:	1 HDMI out

BATTERY

Battery:	24V compatible with external power supply and V-Mounts batteries (14.4-28.8Vdc) - battery not included

ELECTRICAL

Low Voltage DC mains:	24V via DC IN through external power supply, 14,4-28,8V with V-Lock batteries connection
Max power consumption (230V):	40W
Standby power:	23 W

CONNECTIONS

Signal connection:	2 x Seetronic XLR 5p OUT connector
Wireless Connection:	2x integrated LumenRadio TiMoTwo - CRMX, CRMX² (RX only) and W-DMX compatible
Wireless Antenna:	2 RP-TNC female connector
Data connection:	1 x RJ45 IN/OUT
Data:	3 x USB-A ports (1 on the top, 2 on the back)
Low Voltage DC connector:	XLR 4P for 24V, 2 x V-Mount adapter (14,4V)

PHYSICAL

IP rating:	IP20
Cooling:	passive, fan-free
Housing:	Sturdy polycarbonate body
Finish:	black
Operating temperature:	Ta 0 to +45 °C (+32 to +113 °F)
Dimensions (WxHxD):	374x98x356mm
Weight:	4,1kg

INSTALLATION

Hardware on-board:	tilt adjustment bar

CERTIFICATIONS / REPORTS

Compliance:	CE, RCM, FCC, cTUVus

Downloaded on 27/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x EDGEGO

1 x VDE15BEL010

2 x AEB2DBA

1 x external power supply

ACCESSORIES & RELATED PRODUCTS



AEB2DBA

2 dBi Omni antenna (RP-TNC male connector) for AETHERBOX and CRMXBOXIP67, up to 80 m



VDE15BEL010

Power cable VDE socket, bare-end, 3 X 1,5mm², L.1m



EDGEGOBAG1U

Empty ABS case for 1 pc of EDGEGO

TECHNICAL DRAWINGS

