Halu Rock

ORDER CODE: HALUROCK



SOURCE	IP RATING	WEIGHT
49 (7x7) x3W Warm White LED	**IP20**	**14kg / 30.86lbs**

Downloaded on 07/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	49 (7x7) x3W Warm White LED
Source CCT:	2.800K
Luminous flux:	5'462
Lux:	30'110lx @3 m
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	6°
Field angle:	8°

DYNAMIC EFFECTS

Pixel patterns:	pre-programmed static and dynamic pixel patterns
FX generator:	adjustable foreground/background colour, index, speed, direction
Manual mode:	manual adjustment of dimmer and strobe
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512, Art-Net, Kling-Net
DMX channels:	13 / 16 / 55 / 62 / 65ch
Master/Slave:	for synchronised operation of more units linked in a chain

MOVEMENT

Pan:	540° - 8/16-bit resolution
Tilt:	270° - 8/16-bit resolution
Pan / tilt lock:	for transport and maintenance

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 - 20 flash(s), mechanical

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	Neutrik XLR 3p + 5p IN/OUT connectors

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	202W
Output (at 230V):	8 units on a single power line
Max power consumption (120V):	208W

PHYSICAL

IP rating:	IP20
Cooling:	forced-air with low-noise fan
Housing:	Aluminium structure with high-resistance polycarbonate cover
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	379x471x288mm
Weight:	14kg

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 07/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x HALUROCK

1 x 1,5 meters power cable (BARE END - SEETRONIC power connector)

2 x quick-lock omega brackets

ACCESSORIES & RELATED PRODUCTS



FCLHALUROCK
Flight case for 2 HALUROCK



UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS

