Halu Strip

ORDER CODE: HALUSTRIP



SOURCE	IP RATING	WEIGHT
14x3W Warm White LED	**IP40**	**3,5kg / 7.72lbs**

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	14x3W Warm White LED
Source CCT:	2.800K
Luminous flux:	1'186
Lux:	3'750lx @3 m
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	7°
Field angle:	8°
Pixel pitch:	72mm
Lens type:	HD anti-reflection lenses with achromatic coating

DYNAMIC EFFECTS

Pixel patterns:	pre-programmed static and dynamic pixel patterns
FX generator:	adjustable foreground/background colour, index, speed, direction
Static mode:	selection of static colour
Manual mode:	manual adjustment of dimmer and strobe
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512
DMX channels:	5 / 14 / 19ch
Pixel control:	pixel2pixel control
Display:	Graphic User Interface
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 - 25 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	Amphenol XLR 3p + 5p IN/OUT connectors

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	49W
Output (at 230V):	24 units on a single power line
Max power consumption (120V):	48W

PHYSICAL

IP rating:	IP40
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	1000x169x58mm
Weight:	3,5kg

INSTALLATION

Suspension and fixing:	- bracket for truss rigging and hardware for connection of more units

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA

BOX CONTENT

1 x HALUSTRIP

1 x 1,5 meters power cable (BARE END - NEUTRIK POWERCON)

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS

