Jet Spot2

ORDER CODE: JETSPOT2BK



VERSIONS

	Code	Housing
	**JETSPOT2BK**	**Black**
	JETSPOT2WH	White

SOURCE
150W high-power white LED

IP RATING
IP20

WEIGHT
13,7kg / 30.2lbs

CRI
78

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	150W high-power white LED
Source CCT:	8.000K
Luminous flux:	7'400
Lux:	8'900lx @3 m
Lux:	810lx @10 m
CRI:	78
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	20°
Focus:	motorised 8/16-bit

COLOUR SYSTEM

Colour wheel:	8 colour filters + open

DYNAMIC EFFECTS

Circular prism:	3-f with bi-directional rotation, indexing
Auto mode:	built-in programs with execution speed adjustment

GOBOS

Gobo wheel 1:	7 rotating gobos + open, interchangeable, indexing
Gobo size:	outer: 24,2 mm - image: 20 mm - thickness: 0,3 mm
Fixed gobos:	8 fixed gobos + open

CONTROL

Supported Protocols:	DMX512, RDM
DMX channels:	12 / 15ch
RDM:	for remote addressing and parameter configuration
Display:	Graphic User Interface
Master/Slave:	for synchronised operation of more units linked in a chain

MOVEMENT

Pan:	540° - 8/16-bit resolution
Tilt:	270° - 8/16-bit resolution
Position feedback:	automatic repositioning after external movement

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Strobe / shutter:	1 - 30 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	Seetronic powerCON IN/OUT connectors
Signal connection:	XLR 3p + 5p IN/OUT connectors

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	225W
Output (at 230V):	16 units on a single power line
Max power consumption (120V):	226W
Output (at 120V):	8 units on a single power line

PHYSICAL

IP rating:	IP20
Housing:	Aluminium structure with high-resistance polycarbonate cover
Finish:	black (RAL 9004) or white (RAL 9003)
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	308x436x230mm
Weight:	13,7kg

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x JETSPOT2

1 x 1,5 meters power cable (BARE END - SEETRONIC power connector)

2 x OS24PLUS

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

