Jet Spot3

ORDER CODE: JETSPOT3BK



VERSIONS

	Code	Housing
	**JETSPOT3BK**	**Black**
	JETSPOT3WH	White

SOURCE
240W high-power white LED

IP RATING
IP20

WEIGHT
17,3kg / 38.14lbs

CRI
78

Downloaded on 27/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	240W high-power white LED
Source CCT:	7.500K
Luminous flux:	12'459
Lux:	13'389lx @3 m
Lux:	1'205lx @10 m
CRI:	78
Source life expectancy:	> 30.000 h

OPTICS

Beam angle:	20°
Lens diameter:	74mm
Lens type:	high-quality glass lens optics
Focus:	motorised 8/16-bit

COLOUR SYSTEM

Colour wheel:	7 colour filters on two colour wheels

DYNAMIC EFFECTS

Circular prism:	3-f with bi-directional rotation, indexing
Frost:	linear 0-100%
Iris:	5 ~ 100% motorised iris
Auto mode:	built-in programs with execution speed adjustment

GOBOS

Gobo wheel 1:	7 rotating gobos + open, interchangeable, indexing
Gobo size:	outer: 26,7 mm - image: 23 mm - thickness: min 0.3 mm - max 3mm
Fixed gobos:	8 fixed gobos + open, interchangeable
Gobo size:	outer: 29,6 mm - image: 23 mm - thickness: 0,5 mm

CONTROL

Supported Protocols:	DMX512, RDM
DMX channels:	17 / 19ch
RDM:	for remote addressing and parameter configuration
Display:	Graphic User Interface
Master/Slave:	for synchronised operation of more units linked in a chain

MOVEMENT

Pan:	540° - 16-bit resolution
Tilt:	260° - 16-bit resolution
Position feedback:	automatic repositioning after external movement

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Strobe / shutter:	0 ~ 30 Hz, electronic
Display battery:	included, self-charging battery backup
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	Amphenol XLR 3p + 5p IN/OUT connectors

Downloaded on 27/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	316W
Output (at 230V):	12 units on a single power line
Max power consumption (120V):	322W
Output (at 120V):	6 units on a single power line

PHYSICAL

IP rating:	IP20
Cooling:	forced-air with low-noise fan
Housing:	Aluminium structure with high-resistance polycarbonate cover
Finish:	black or white finishing
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	355x500x257mm
Weight:	17,3kg

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM, cTUVus, FCC

BOX CONTENT

1 x JETSPOT3

1 x 1,5 meters power cable (BARE END - NEUTRIK POWERCON)

2 x OS24PLUS

ACCESSORIES & RELATED PRODUCTS



OS25PLUS

Quick-lock omega bracket, M12 hole

TECHNICAL DRAWINGS

