LumiPar 18QIP

ORDER CODE: **LUMIPAR18QIP**



SOURCE	IP RATING	WEIGHT
18x8W RGBW LED	**IP65 for temporary outdoor use**	**5,5kg / 12.13lbs**

Downloaded on 23/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	18x8W RGBW LED
Luminous flux:	5439
Lux:	(15°) 4145lx @3 m full
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	15°
Field angle:	30°
Lens diameter:	42mm
Additional optics:	25° and 45° (optional)

COLOUR SYSTEM

White presets:	3200~10000K
Colour wheel:	virtual colour wheel with macros
Macros:	built-in white presets

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512
DMX channels:	4/6/10ch
Display:	LCD display
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	5 selectable dimming modes available
Strobe / shutter:	1-25 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	IP IN/OUT power connector
Signal connection:	IP IN/OUT DMX connector
Adaptors:	XLR and BARE END 16A adaptors included

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	123W
Output (at 230V):	16 units on a single power line
Max power consumption (120V):	125W

PHYSICAL

IP rating:	IP65 for temporary outdoor use
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta -20 to +45 °C (-4 to +113 °F)
Dimensions (WxHxD):	349x280x273mm
Weight:	5,5kg

INSTALLATION

Suspension and fixing:	double bracket for hanging and floor positioning

Downloaded on 23/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



ARCLUMIL25D42
Optic lens 25°, D.42mm



ARCLUMIL45D42
Optic lens 45°, D.42mm



UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS

