Lumipar18qpro

ORDER CODE: **LUMIPAR18QPRO25**



VERSIONS

	Code	Beam angle
	**LUMIPAR18QPRO25**	**25°**
	LUMIPAR18QPRO45	45°

SOURCE	IP RATING	WEIGHT
18x8W RGBW LED	**IP44**	**5kg / 11.02lbs**

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	18x8W RGBW LED
Luminous flux:	3577
Lux:	(25°) 1758lx @3 m full
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	(18QPRO25) 25°, (18QPRO45) 45°
Field angle:	(18QPRO25) 38°, (18QPRO45) 50°

COLOUR SYSTEM

White presets:	3200~10000K
Colour wheel:	virtual colour wheel with macros
Macros:	built-in white presets

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512
DMX channels:	4 / 6 / 10ch
Display:	LCD display
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	5 selectable dimming modes available
Strobe / shutter:	1-25 Hz, electronic

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	3p IN/OUT

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	118W
Output (at 230V):	12 units on a single power line
Max power consumption (120V):	121W

PHYSICAL

IP rating:	IP44
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	302x239x259mm
Weight:	5kg

INSTALLATION

Suspension and fixing:	double bracket for hanging and floor positioning

ACCESSORIES & RELATED PRODUCTS



ARCLUMIL25D38
Optic lens 15°, D.38mm



ARCLUMIL45D38
Optic lens 45°, D.38mm

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

