Lumipar7vwpro

ORDER CODE: LUMIPAR7VWPRO



SOURCE	IP RATING	WEIGHT
7x6W Warm White + Cold White LEDs	**IP44**	**2,5kg / 5.51lbs**

Downloaded on 28/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	7x6W Warm White + Cold White LEDs
Source CCT:	3000-6000K
Luminous flux:	1339
Lux:	1290lx @3 m
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	25°
Field angle:	39°
Lens diameter:	38mm
Additional optics:	45° (optional)

COLOUR SYSTEM

Colour mixing:	tunable white
CCT:	linear CTO correction 2.700 K ~ 6.000 K
White presets:	3000~6000K

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512
DMX channels:	2 / 3 / 7ch
Display:	LCD display
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	5 selectable dimming modes available
Strobe / shutter:	1-25 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	3p IN/OUT

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	36W
Output (at 230V):	32 units on a single power line
Max power consumption (120V):	36W

PHYSICAL

IP rating:	IP44
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	white
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	228x184x208mm
Weight:	2,5kg

INSTALLATION

Suspension and fixing:	double bracket for hanging and floor positioning

ACCESSORIES & RELATED PRODUCTS



ARCLUMIL45D38
Optic lens 45°, D.38mm



UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS

