Mini **Ruby**

ORDER CODE: MINIRUBY



SOURCE
132W S Osram Sirius HRI

IP RATING
IP30

WEIGHT
7,6kg / 16.76lbs

CRI
60

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	132W S Osram Sirius HRI
Source CCT:	9.200K
Luminous flux:	5'150
Lux:	98'792lx @5 m full
CRI:	60
Source life expectancy:	6.000 h

OPTICS

Beam angle:	3,5°
Field angle:	3,5°
Lens diameter:	80mm
Lens type:	high-quality glass lens optics

COLOUR SYSTEM

Colour wheel:	9 colour filters + open

DYNAMIC EFFECTS

Circular prism:	8-f with bi-directional rotation

CONTROL

Supported Protocols:	DMX512, RDM
DMX channels:	7 / 9ch
Display:	LCD display
Hibernation:	power safe mode when lost DMX
Master/Slave:	for synchronised operation of more units linked in a chain

MOVEMENT

Pan:	540 / 630° - 8/16-bit resolution
Tilt:	265° - 8/16-bit resolution
Position feedback:	automatic repositioning after external movement

ELECTRONICS

Strobe / shutter:	1 - 28 flash(s), mechanical
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX2 (not included)

CONNECTIONS

Power connection:	Neutrik powerCON IN/OUT connectors
Signal connection:	Amphenol XLR 3p + 5p IN/OUT connectors

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	176W
Output (at 230V):	12 units on a single power line
Max power consumption (120V):	176W

PHYSICAL

IP rating:	IP30
Cooling:	heat pipe with low-noise fan
Housing:	Aluminium structure with high-resistance polycarbonate cover
Finish:	black
Operating temperature:	Ta -10 to +45 °C (+14 to +113 °F)
Dimensions (WxHxD):	278x387x200mm
Weight:	7,6kg

INSTALLATION

Suspension and fixing:	any position with quick-lock Omega brackets

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x MINIRUBY

1 x 1,5 meters power cable (BARE END - NEUTRIK POWERCON)

1 x OS24PLUS

ACCESSORIES & RELATED PRODUCTS



OS24PLUS
Quick-lock omega bracket, M12 hole



FCLMINIRUBY
Flight case for 6 pcs of MINIRUBY



UPBOXPRO
Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

