Modulaspot

ORDER CODE: **MODULASPOTFC**



VERSIONS

Code	Quantity	Source	Colour	Beam angle
MODULASPOTFC	**2**	**10 W LED**	**RGBW**	**15°**
MODULASPOTDY	2	3 W LED	White 5600K	15°

SOURCE
(FC) RGBW 10 W - (DY) 3W

WEIGHT
0,25kg / 0.55lbs

LUMINOUS FLUX (MAX)
194 lm

CRI
(DY) 70,9 - (FC) 37,6

Downloaded on 18/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	(FC) RGBW 10 W - (DY) 3W
Source CCT:	(DY) 5.600K
Luminous flux:	(1xDY) 194 lm - (1xFC) 254
Lux:	(1xDY) 5.320 lux - (1xFC) 5.150lx @1 m full
Lux:	(1xDY) 477 lux - (1xFC) 453lx @3 m full
CRI:	(DY) 70,9 - (FC) 37,6
Other:	Max 6pc MODULASPOT per SMARTMODULA
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	15°
Field angle:	23°

ELECTRICAL

Max power consumption (230V):	(Single FC) 5,5 W - (Full FC) 33 W - (Single DY) 1,5 W - (Full DY) 9W

PHYSICAL

Dimensions (WxHxD):	80x80x110mm
Weight:	0,25kg

CERTIFICATIONS / REPORTS

Compliance:	CE

BOX CONTENT

2 x MODULASPOT

ACCESSORIES & RELATED PRODUCTS



MSPOT12CASE

ABS case to contain 12xMODULASPOT



UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

Downloaded on 18/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

