Modulawash

ORDER CODE: **MODULAWASHDY**



VERSIONS

	Code	Quantity	Source	Colour	Beam angle
	MODULAWASHFC	1	25 W LED	RGBW	60°
	**MODULAWASHDY**	**1**	**25 W LED**	**White 4000K**	**60°**

SOURCE
(FC) RGBW 12x6 W - (DY) 12x3W

WEIGHT
1kg / 2.2lbs

LUMINOUS FLUX (MAX)
1.213 lm

CRI
(DY) 81

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	(FC) RGBW 12x6 W - (DY) 12x3W
Source CCT:	(DY) 6.400K
Luminous flux:	(DY) 1.213 lm
Luminous flux:	(FC) 2.778 lm
Lux:	(DY) 3.800 lux - (FC) 8.340lx @1 m full
Lux:	(DY) 468 lux - (FC) 1110lx @3 m full
CRI:	(DY) 81
Other:	Max 1pc MODULAWASH per SMARTMODULA (+2pcs SPOT)
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	60°
Field angle:	65°

ELECTRICAL

Max power consumption (230V):	(Single FC) 27 W - (Single DY) 15W

CERTIFICATIONS / REPORTS

Compliance:	CE

PHYSICAL

Dimensions (WxHxD):	500x55x55mm
Weight:	1kg

BOX CONTENT

1 x MODULAWASH

ACCESSORIES & RELATED PRODUCTS



MWASH04CASE

ABS case to contain 04xMODULAWASH



UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector

TECHNICAL DRAWINGS

