Smart BatIP

ORDER CODE: SMARTBATIP



SOURCE	IP RATING	WEIGHT
4x8W RGBW LEDs	**IP54 for temporary outdoor use**	**3,6kg / 7.94lbs**

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	4x8W RGBW LEDs
Lux:	980lx @3 m full
Source life expectancy:	> 50.000 h

COLOUR SYSTEM

White presets:	3200 K ~ 10.000K
Colour wheel:	virtual colour wheel with macros

CONTROL

Supported Protocols:	DMX512
DMX channels:	4 / 6 / 10ch
Display:	LED display user interface
IR:	infrared sensor controlled by remote
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 - 25 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz
Max power consumption (230V):	43W

INSTALLATION

Mounting points:	M12 threaded mounting points

OPTICS

Beam angle:	23°
Lens diameter:	42mm
Additional optics:	25° and 45° optional

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

MOVEMENT

Tilt:	(up to) 20° with adjustable foot support

CONNECTIONS

Power connection:	IEC 10 A IN
Wireless Connection:	integrated WIBOX, WDBOX proprietary protocol

BATTERY

Battery:	11,1V lithium
Battery life in colour change mode up to:	12h
Battery life in full-mode up to:	6h
Recharge connection:	power cable
Recharge time:	5h (max)
Battery level indicator:	shown on display

PHYSICAL

IP rating:	IP54 for temporary outdoor use
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta 0 to +40 °C (+32 to +104 °F)
Dimensions (WxHxD):	138x191x145mm
Weight:	3,6kg

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x SMARTBATIP

1 x 1,5 meters BARE END - IEC power cable

1 x LUMIPARIRCH

ACCESSORIES & RELATED PRODUCTS



LUMIPARIRCH

RGBWA IR remote controller, manual / auto modes, for LUMIPAR IR series



FCLSMARTBAT

Flight case for 9 SMARTBAT, 613x480x507 mm, 22 kg



SMARTCOVERMR

Mirror housing for SMARTBAT projectors.



SMARTBATCOVER

Nylon rain-proof cover for SMARTBAT projector



SMARTBATBAGI

New nylon bag high resistance to contain 4 pcs SMARTBAT projectors.



ARCLUMIL25D42

Optic lens 25°, D.42mm



ARCLUMIL45D42

Optic lens 45°, D.42mm

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

