Tabled C

ORDER CODE: TABLED-C



VERSIONS

	Code	Tabled	Extensions	Bases	Recharger	IRC	Certifications
	**TABLED-C**	**x1**	**No**	**x1 TABLEDDSK22W**	**1x1**	**No**	**CE, UKCA, RCM**
	TABLED-CPACK	x4	x2 TABLEDEXT-027	x4 TABLEDDSK22W	1x4	x1	CE, UKCA, RCM
	TABLED-CPACKWH	x4	x2 TABLEDEXT-027WH	x4 TABLEDDSK22W	1x4	x1	CE, UKCA, RCM

SOURCE
6x3 W + 6x1W RGB + Neutral White

IP RATING
IP30

WEIGHT
1,18kg / 2.6lbs

CRI
80

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	6x3 W + 6x1W RGB + Neutral White
Source CCT:	NW 4.000K
CRI:	80
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	360° designed to light up standard 160/180 cm ceremony tables

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour

CONTROL

Supported Protocols:	W-DMX
DMX channels:	4 / 7 / 10 / 12ch
Display:	Graphic User Interface
IR:	infrared sensor controlled by remote (included in the pack, not included in single unit)

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 - 30 Hz, electronic
Firmware upgrade with:	via DMX with UPBOX1U (not included)

BATTERY

Battery:	2,20 Ah - 14,8V lithium
Battery life in colour change mode up to:	14,5h
Battery life in single colour mode up to:	R: 19 h - G: 17,5 h - B: 17,5 h - W: 17,5h
Battery life in full-mode up to:	9h
Recharge connection:	power cable fast-charge in pelican case
Recharge time:	4h (max)
Battery level indicator:	shown on display

CONNECTIONS

Wireless Connection:	integrated W-DMX receiver
Data connection:	W-DMX receiver

ELECTRICAL

Mains power supply:	DC 24 V - 1 A
Max power consumption (230V):	8,8W

PHYSICAL

IP rating:	IP30
Housing:	Sturdy die-cast aluminium body
Finish:	white (RAL 9003) or mirror
Operating temperature:	Ta 0 to +45 °C (+32 to +113 °F)
Dimensions (WxHxD):	140x307x220mm
Weight:	1,18kg

INSTALLATION

Suspension and fixing:	magnetic base to attach on every metal surface
Hardware on-board:	magnetic base

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

4 x TABLED-C

2 x TABLEDEXT-027

4 x TABLEDDSK22W

1 x Charger for 4 Tab

ACCESSORIES & RELATED PRODUCTS



AETHERBOXONE

IP65 1x universe CRMX transceiver, DMX, Ethernet protocols, Wi-Fi, Bluetooth, battery-ready, POE



PRL-IRC

RGBWA IR controller, 29 buttons, manual/static colours, auto programs, fade

TABLEDDSK22W

White disk for TABLED, D 220 mm



TABLEDDSK22MT

Transparent disk with magnet for TABLED, D 220 mm

TABLEDDSK28MW

White disk with magnet for TABLED, D 280 mm

TABLEDDSK40MW

White disk with magnet for TABLED, D 400 mm

Downloaded on 26/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

