Tabled W

ORDER CODE: TABLED-W



VERSIONS

	Code	Tabled	Extensions	Bases	Recharger	IRC
	**TABLED-W**	**x1**	**No**	**x1 TABLEDDSK22W**	**1x1**	**No**
	TABLED-WPACK	x4	x2 TABLEDEXT-027	x4 TABLEDDSK22W	1x4	x1

SOURCE

6x1 W + 6x1W Warm White + Cold White LEDs

IP RATING

IP30

WEIGHT

1,16kg / 2.56lbs

CRI

80

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	6x1 W + 6x1W Warm White + Cold White LEDs
Source CCT:	3.200 K - 5.600K
CRI:	80
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	360° designed to light up standard 160/180 cm ceremony tables

COLOUR SYSTEM

Colour mixing:	tunable white

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour

CONTROL

IR:	infrared sensor controlled by remote (included in the pack, not included in single unit)

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Strobe / shutter:	1 - 30 Hz, electronic
Firmware upgrade with:	via DMX with UPBOX1U (not included)

BATTERY

Battery:	2.200 m Ah - 14,8V lithium
Battery life in single colour mode up to:	W: 14h - A: 14,5h
Battery life in full-mode up to:	8h
Recharge connection:	power supply
Recharge time:	4h (max)
Battery level indicator:	LED battery status indicator

CONNECTIONS

Data connection:	infrared sensor controlled

ELECTRICAL

Mains power supply:	DC 24 V, 1 A, 24 W
Max power consumption (230V):	9W

PHYSICAL

IP rating:	IP30
Housing:	Sturdy die-cast aluminium body
Finish:	mirror finishing
Operating temperature:	Ta 0 to +45 °C (+32 to +113 °F)
Dimensions (WxHxD):	140x307x220mm
Weight:	1,16kg

INSTALLATION

Suspension and fixing:	magnetic base to attach on every metal surface
Hardware on-board:	magnetic base

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

ACCESSORIES & RELATED PRODUCTS



PRL-IRC
RGBWA IR controller, 29 buttons, manual/static colours, auto programs, fade

TABLEDDSK22W
White disk for TABLED, D 220 mm



TABLEDDSK22MT
Transparent disk with magnet for TABLED, D 220 mm

TABLEDDSK28MW
White disk with magnet for TABLED, D 280 mm

TABLEDDSK40MW
White disk with magnet for TABLED, D 400 mm



TABUPBOXI
Interface used between UPBOX1U and TABLED for make firmware upgrade

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

