Z 8Strip

ORDER CODE: Z8STRIP



SOURCE	IP RATING	WEIGHT
8x10W RGBW LEDs	**IP65 (front) - IP54 (bottom) for temporary outdoor use**	**10kg / 22.05lbs**

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source:	8x10W RGBW LEDs
Luminous flux:	1'064
Lux:	4'600lx @3 m full
Source life expectancy:	> 50.000 h

OPTICS

Beam angle:	10°
Field angle:	21°
Other:	magnetic holder for diffusion filters or gels

COLOUR SYSTEM

White presets:	3.200 K ~10.000K
Colour wheel:	virtual colour wheel with macros
Macros:	built-in white presets

DYNAMIC EFFECTS

Static mode:	selection of static colour
Manual mode:	manual adjustment of colour
Auto mode:	built-in programs with execution speed adjustment

CONTROL

Supported Protocols:	DMX512, W-DMX
DMX channels:	4 / 6 / 10 / 32 / 37ch
Pixel control:	pixel2pixel control
Display:	black OLED touch display
Master/Slave:	for synchronised operation of more units linked in a chain

ELECTRONICS

Dimmer:	linear 0 - 100% electronic dimmer
Dimmer curves:	4 selectable dimming modes available
Strobe / shutter:	1 - 25 Hz, electronic
Firmware upgrade with:	via DMX with UPBOXPRO/ UPBOX1 (not included)

BATTERY

Battery:	14,8V lithium
Battery life in colour change mode up to:	16h
Battery life in single colour mode up to:	R: 16 h - G: 12,5 h - B: 13 h - W: 13h
Battery life in full-mode up to:	6h
Recharge connection:	power cable
Recharge time:	5h (max)
Battery level indicator:	shown on display

CONNECTIONS

Power connection:	Seetronic powerCON waterproof IN/OUT connectors
Signal connection:	Seetronic XLR 5p IN/OUT connectors
Wireless Connection:	integrated W-DMX receiver
Data connection:	W-DMX receiver

ELECTRICAL

Mains power supply:	100-240V - 50/60Hz

PHYSICAL

IP rating:	IP65 (front) - IP54 (bottom) for temporary outdoor use
Cooling:	fan-free with natural convection
Housing:	Sturdy die-cast aluminium body
Finish:	black
Operating temperature:	Ta 0 to +45 °C (+32 to +113 °F)
Dimensions (WxHxD):	801x216x153mm
Weight:	10kg

INSTALLATION

Suspension and fixing:	bracket for hanging and floor positioning

CERTIFICATIONS / REPORTS

Compliance:	CE, UKCA, RCM

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL SPECIFICATIONS

BOX CONTENT

1 x Z8STRIP

1 x 1,5 meters power cable (BARE END - SEETRONIC IP65 power connector)

ACCESSORIES & RELATED PRODUCTS



AETHERBOXONE

IP65 1x universe CRMX transceiver, DMX, Ethernet protocols, Wi-Fi, Bluetooth, battery-ready, POE



UPBOXPRO

Firmware uploader kit, USB IN, 5-pin XLR DMX OUT connector



ARCLUMIL15D45

Optic lens 15°, D.45mm



ARCLUMIL25D45

Optic lens 25°, D.45mm

Downloaded on 29/11/2026 - data may be provisional: features, specifications and appearance are subject to change without notice

TECHNICAL DRAWINGS

