Iptestbox

ORDER CODE: IPTESTBOX



WEIGHT

7kg / 15.43lbs

CARATTERISTICHE PRINCIPALI

- Test according to a specific PROLIGHTS product program, or according to an IP class
- Continuous stress test mode with multiple cycles
- Save and load report from SD card
- Generating reports with fixture name, serial number and date/time of test
- Report readable in CSV format
- Import/Export settings
- Unit Auto test for self diagnostic of the IPTESTBOX
- Firmware upgrade through SD card

SPECIFICHE TECNICHE

CONTROLLO

Display:	Graphic User Interface

ELETTRONICA

Aggiornamento firmware con:	tramite menu con memoria SD interna

CONNESSIONI

Connessione di alimentazione:	Neutrik powerCON TRUE1 IN connector

ALIMENTAZIONE

Alimentazione elettrica:	100-240V - 50/60Hz
Potenza massima assorbita (230V):	40W

CARATTERISTICHE FISICHE

Finitura:	nero (RAL 9004)
Temperatura d'esercizio:	Ta -20 - +45 °C
Dimensioni (LxAxP):	420x362x165mm
Peso:	7kg

BOX CONTENT

1 x IPTESTBOX

1 x flexible tube

1 x M12 thread adapter

1 x cap with M12 thread

ACCESSORI E PRODOTTI CORRELATI



IPTBM6ADP

Adattatore M6 e tappo M6 per IPTESTBOX

TECHNICAL DRAWINGS

